

# **autOTEK<sup>®</sup>**

**EVOLUTION OF POWER**  
**2010 PRODUCT LINE**

AT AMPLIFIERS	PERFORMANCE	Dimensions
AT1000	250 x 2 @ 4 OHMS, 500 x 2 @ 2 OHMS - 1000 WATTS x 1 @ 4 OHMS	9.85 x 9.85 x 2.17
AT1500	375 x 2 @ 4 OHMS, 750 x 2 @ 2 OHMS - 1500 WATTS x 1 @ 4 OHMS	12.6 x 9.85 x 2.17
AT2500	625 x 2 @ 4 OHMS, 1250 x 2 @ 2 OHMS - 2500 WATTS x 1 @ 4 OHMS	14.96 x 9.85 x 2.17
FOUR CHANNEL		
AT1200	150 x 4 @ 4 OHMS, 300 x 4 @ 2 OHMS - 600 x 2 @ 4 OHMS	10.24 x 9.85 x 2.17
AT950	110 x 4 @ 4 OHMS, 210 x 4 @ 2 OHMS - 425 x 2 @ 4 OHMS	9.05 x 9.85 x 2.17
Mono Blocks		
AT2000.1	1 x 500 @ 4 OHMS, 1 x 1000 @ 2 OHMS, 1 x 2000 @ 1 OHM A/B Class	15.75 x 9.85 x 2.17

- SEPP A/B Analog Class
- 4/2 Ohm Stable
- Multi-Channel 4/3/2/1 Channel Configurable
- PWM Power Supply
- Fully Adjustable Crossovers



AT SPEAKERS	PERFORMANCE
AT6.2C	250 WATTS MAXIMUM 50 NOMINAL 6.5" 2 WAY COMP
AT62CX	250 WATTS MAXIMUM 50 NOMINAL 6.5" COAXIAL
AT692	375 WATTS MAXIMUM 70 NOMINAL 6 X 9" OVAL 2 WAY
AT693	375 WATTS MAXIMUM 70 NOMINAL 6 X 9" OVAL 3 WAY

- Impact resistant tweeter elements
- Neo-Mylar soft dome tweeter
- External 12 dB passive in-line crossover with component set
- Raised T-yoke
- Alpha-cellulose cones
- Spade-style speaker terminals
- Moisture-resistant rubber surround
- High mid-bass impact
- Anti-resonant stamped steel basket
- All installation hardware included



AT SUBWOOFERS	PERFORMANCE
AT12D2	12" DVC 2 OHM - 600 WATTS MAXIMUM 300 RMS
AT12D4	12" DVC 4 OHM - 600 WATTS MAXIMUM 300 RMS

- 12-inch DVC subwoofer
- Dual 4-Ohm, dual 2-Ohm
- High-energy magnet
- Paper cone
- Ultra rigid stamped steel basket
- Multi-layer high-temp voice coil
- Front-plate and voice-coil cooling
- Integrated spider tinsel-lead design
- Foam surround



STREET MACHINE AMPLIFIERS	PERFORMANCE	Dimensions
SM2-400	2 x 100 @ 4 OHMS, 2 x 200 @ 2 OHMS - 1 x 400 WATTS @ 4 OHMS	10.24 x 9.4 x 2.3
SM2-1000	2 x 250 @ 4 OHMS, 2 x 500 @ 2 OHMS - 1 x 1000 WATTS @ 4 OHMS	14.96 x 9.4 x 2.3
SM2-1200	2 x 300 @ 4 OHMS, 2 x 600 @ 2 OHMS - 1 x 1200 WATTS @ 4 OHMS	14.96 x 9.4 x 2.3
SM2-3500	2 x 875 @ 4 OHMS, 2 x 1750 @ 2 OHMS - 1 x 3500 WATTS @ 4 OHMS	14.96 x 9.4 x 2.3
FOUR CHANNEL		
SM4-800	4 x 100 @ 4 OHMS, 4 x 200 @ 2 OHMS - 2 x 400 @ 4 OHMS	13.39 x 9.4 x 2.3
SM4-1000	4 x 125 @ 4 OHMS, 4 x 250 @ 2 OHMS - 2 x 500 @ 4 OHMS	14.96 x 9.4 x 2.3
MONO BLOCK A/B		
SM1-1000	1 x 250 @ 4 OHMS, 1 x 500 @ 2 OHMS - 1 x 1000 WATTS @ 1 OHM MONO	18.11 x 9.4 x 2.3
SM1-1500	1 x 375 @ 4 OHMS, 1 x 750 @ 2 OHMS - 1 x 1500 WATTS @ 1 OHM MONO	20.08 x 9.4 x 2.3
SM 12D4	12" DVC 4 OHM - 600 WATTS MAXIMUM 300 RMS SUBWOOFER	

- SEPP A/B Analog Class
- 4/2 Ohm Stable
- Multi-Channel 4/3/2/1 Channel Configurable
- PWM Power Supply
- Fully Adjustable Crossovers Include
  - 24 dB Low Pass
  - 24 dB Subsonic Filter
- Bass Thrust with Variable Bass Equalization



SIREN FULL RANGE	PERFORMANCE
ATS6.5-4	6.5" 4 Ohm Full Range High Output Speaker - Sold as singles
ATS8	8" 4 Ohm Full Range High Output Speaker - Sold as singles
AT46-8	2" 100 Watt RMS Super Tweeter 8Ohms 102dB! Output

- Full Range High Output Speaker
- Sold as Singles
- 1.5" Voice Coil
- 4 Ohm Single Voice Coil
- Spade Terminals
- Stamped Steel Basket
- 29 oz Magnet
- Treated Pressed Paper Cone
- Cloth "W" Surround
- Polished Aluminum Phase Plug
- Poly Cotton Spider



**SIREN**

AT ACCESSORIES	PERFORMANCE
7007	1/2 DIN FOUR BAND TWO-WAY EQ/CROSSOVER WITH 9 V LINE DRIVER
ATK2/3X	HIDE-AWAY TWO OR THREE-WAY ACTIVE CROSSOVER WITH 8.5 V LINE DRIVER



# autOTEK®

## EVOLUTION OF POWER



**MAXXSONICS**  
Maxxsonics® USA, Inc.  
1290 Ensell Road  
Lake Zurich Illinois 60047 USA  
Phone: 847-540-7700  
FAXX: 847-540-9776

www.maxxsonics.com  
MB Quart,® Autotek,® Hifonics®  
and Crunch® USA are divisions of  
Maxxsonics® USA Inc.

**Visit Us On The Web @**  
**maxxsonics.com**  
**myspace.com/maxxsonicsusa**  
**youtube.com/MaxxsonicsUSAInc**

©2009 Maxxsonics USA, Inc.  
All Rights Reserved  
Specifications And Designs Are Subject To Change Without Notice.